

AFFORDABLE PERFORMANCE



WCE 4-Flute End Mill

Versatile Solid Carbide End Mills



COMPLETE
METALWORKING
SOLUTIONS

(800) 991-4225

www.ahbinc.com

ISO Certified

customerservice@ahbinc.com

WIDIA 

WCE END MILLS



AFFORDABLE PERFORMANCE

The WCE 4-flute solid end milling line features an advanced geometry to enable material versatility for end users seeking a cost-effective solution while machining small batches.

The WCE 4-flute geometry combines the asymmetrical index and variable helix features at an affordable price while ensuring material and application versatility while still performing demanding operations like full slots and heavy cuts.



WCE4

Metric: 3mm–20mm

- Sharp edges
- Ball nose
- Radiused
- Chamfered

4-Flute End Mill for Versatile Applications

- Asymmetrical pitch to cut harmonics and reduce vibrations
- Variable helix to reduce vibrations and increase overall stability
- Eccentric relief to provide vibration dampening and increase tool life in Stainless Steel applications
- Core taper for improve chip evacuation and tool stability

WCE4

Versatile Solid Carbide End Mills • WCE4

- TiAlN coating in new WU20PE grade
- Designed to perform on Steel, Stainless Steel and Cast Iron applications
- Asymmetrical pitch to cut harmonics and reduce vibrations
- Variable helix to reduce vibrations and increase overall stability
- Eccentric relief to provide vibration dampening and increase tool life in Stainless Steel applications
- Core taper for improve chip evacuation and tool stability

Materials



Versatile

Capable of working on Steel, Stainless Steel and Cast Iron materials



Reliable

Continuous performance due to asymmetrical index between flutes enabling a reduction in vibrations

Advanced

Advanced geometry design to provide steady performance

WCE4 • Series W401 • Sharp Edge • 4 Flute • Cylindrical Shank • Metric





● first choice
○ alternate choice

WU20PE

order #	catalog #	D1	D	length of cut Ap1 max	length L	Z U
6945502	W401M03003SZT	3,0	6	8,00	57	4
6945503	W401M04003SZT	4,0	6	11,00	57	4
6945504	W401M05003SZT	5,0	6	13,00	57	4
6945505	W401M06003SZT	6,0	6	13,00	57	4
6945548	W401M08004SZT	8,0	8	19,00	63	4
6945549	W401M10005SZT	10,0	10	22,00	72	4
6945684	W401M12006SZT	12,0	12	26,00	83	4
6945685	W401M16008SZT	16,0	16	32,00	92	4
6945686	W401M20009SZT	20,0	20	38,00	104	4

WCE4 • Series W401 • Sharp Edge • 4 Flute • Weldon® Shank • Metric





● first choice
○ alternate choice

WU20PE

order #	catalog #	D1	D	length of cut Ap1 max	length L	Z U
6945510	W401M03003SZW	3,0	6	8,00	57	4
6945541	W401M04003SZW	4,0	6	11,00	57	4
6945542	W401M05003SZW	5,0	6	13,00	57	4
6945543	W401M06003SZW	6,0	6	13,00	57	4
6945562	W401M08004SZW	8,0	8	19,00	63	4
6945563	W401M10005SZW	10,0	10	22,00	72	4
6945690	W401M12006SZW	12,0	12	26,00	83	4
6945691	W401M16008SZW	16,0	16	32,00	92	4
6945692	W401M20009SZW	20,0	20	38,00	104	4

WCE4 • Series W401 • Chamfered • 4 Flute • Cylindrical Shank • Metric





WU20PE

● first choice
○ alternate choice

order #	catalog #	D1	D	length of cut Ap1 max	length L	BCH	Z U
6945506	W401M03003CAT	3,0	6	8,00	57	0,40	4
6945507	W401M04003CAT	4,0	6	11,00	57	0,40	4
6945508	W401M05003CAT	5,0	6	13,00	57	0,40	4
6945509	W401M06003CAT	6,0	6	13,00	57	0,40	4
6945550	W401M08004CAT	8,0	8	19,00	63	0,40	4
6945561	W401M10005CET	10,0	10	22,00	72	0,50	4
6945687	W401M12006CET	12,0	12	26,00	83	0,50	4
6945688	W401M16008CET	16,0	16	32,00	92	0,50	4
6945689	W401M20009CET	20,0	20	38,00	104	0,50	4

WCE4 • Series W401 • Chamfered • 4 Flute • Weldon® Shank • Metric





WU20PE

● first choice
○ alternate choice

order #	catalog #	D1	D	length of cut Ap1 max	length L	BCH	Z U
6945544	W401M03003CAW	3,0	6	8,00	57	0,40	4
6945545	W401M04003CAW	4,0	6	11,00	57	0,40	4
6945546	W401M05003CAW	5,0	6	13,00	57	0,40	4
6945547	W401M06003CAW	6,0	6	13,00	57	0,40	4
6945564	W401M08004CAW	8,0	8	19,00	63	0,40	4
6945565	W401M10005CEW	10,0	10	22,00	72	0,50	4
6945693	W401M12006CEW	12,0	12	26,00	83	0,50	4
6945694	W401M16008CEW	16,0	16	32,00	92	0,50	4
6945695	W401M20009CEW	20,0	20	38,00	104	0,50	4

WCE4 • Series W4N1 • Radiused • 4 Flute • Necked • Cylindrical Shank • Metric





● first choice
○ alternate choice

WU20PE

order #	catalog #	D1	D	D3	length of cut Ap1 max	length L	L3	Re	Z U
6945620	W4N1M03003RAT	3,0	6	2,82	8,00	57	15,00	0,20	4
6945631	W4N1M04003RAT	4,0	6	3,76	11,00	57	16,00	0,20	4
6945632	W4N1M04003RET	4,0	6	3,76	11,00	57	16,00	0,50	4
6945633	W4N1M05003RAT	5,0	6	4,70	13,00	57	18,00	0,20	4
6945634	W4N1M05003RET	5,0	6	4,70	13,00	57	18,00	0,50	4
6945635	W4N1M05003RJT	5,0	6	4,70	13,00	57	18,00	1,00	4
6945636	W4N1M06003RET	6,0	6	5,64	13,00	57	21,00	0,50	4
6945638	W4N1M06003RHT	6,0	6	5,64	13,00	57	21,00	1,50	4
6945637	W4N1M06003RJT	6,0	6	5,64	13,00	57	21,00	1,00	4
6945640	W4N1M08004RET	8,0	8	7,52	19,00	63	27,00	0,50	4
6945642	W4N1M08004RHT	8,0	8	7,52	19,00	63	27,00	1,50	4
6945641	W4N1M08004RJT	8,0	8	7,52	19,00	63	27,00	1,00	4
6945643	W4N1M08004RKT	8,0	8	7,52	19,00	63	27,00	2,00	4
6945644	W4N1M10005RET	10,0	10	9,40	22,00	72	32,00	0,50	4
6945646	W4N1M10005RHT	10,0	10	9,40	22,00	72	32,00	1,50	4
6945645	W4N1M10005RJT	10,0	10	9,40	22,00	72	32,00	1,00	4
6945647	W4N1M10005RKT	10,0	10	9,40	22,00	72	32,00	2,00	4
6945128	W4N1M12006RET	12,0	12	11,28	26,00	83	38,00	0,50	4
6945130	W4N1M12006RHT	12,0	12	11,28	26,00	83	38,00	1,50	4
6945129	W4N1M12006RJT	12,0	12	11,28	26,00	83	38,00	1,00	4
6945481	W4N1M12006RKT	12,0	12	11,28	26,00	83	38,00	2,00	4
6945482	W4N1M12006RQT	12,0	12	11,28	26,00	83	38,00	4,00	4
6945483	W4N1M16008RJT	16,0	16	15,04	32,00	92	44,00	1,00	4
6945484	W4N1M16008RKT	16,0	16	15,04	32,00	92	44,00	2,00	4
6945485	W4N1M16008RPT	16,0	16	15,04	32,00	92	44,00	3,00	4
6945486	W4N1M16008RQT	16,0	16	15,04	32,00	92	44,00	4,00	4
6945487	W4N1M20009RJT	20,0	20	18,80	38,00	104	53,00	1,00	4
6945488	W4N1M20009RKT	20,0	20	18,80	38,00	104	53,00	2,00	4
6945489	W4N1M20009RPT	20,0	20	18,80	38,00	104	53,00	3,00	4
6945490	W4N1M20009RQT	20,0	20	18,80	38,00	104	53,00	4,00	4

WCE4 • Series W411 • Chamfered • 4 Flute • Long Length • Cylindrical Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalog #	D1	D	length of cut Ap1 max	length L	BCH	Z U
6946013	W411M06013CAT	6,0	6	32,00	76	0,40	4
6946014	W411M08014CAT	8,0	8	32,00	87	0,40	4
6946015	W411M10015CET	10,0	10	38,00	89	0,50	4
6946046	W411M12016CET	12,0	12	51,00	100	0,50	4
6946047	W411M16018CET	16,0	16	57,00	125	0,50	4
6946048	W411M20019CET	20,0	20	57,00	125	0,50	4

WCE4 • Series W4NB • Ball Nose • 4 Flute • Cylindrical Shank • Metric





WU20PE

- first choice
- alternate choice

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Z U
6945882	W4NBM05003RBT	5,0	6	4,70	13,00	57	18,00	4
6945883	W4NBM06003RBT	6,0	6	5,64	13,00	57	21,00	4
6945886	W4NBM08004RBT	8,0	8	7,52	19,00	63	27,00	4
6945887	W4NBM10005RBT	10,0	10	9,40	22,00	72	32,00	4
6945895	W4NBM12006RBT	12,0	12	11,28	26,00	83	30,00	4
6945896	W4NBM16008RBT	16,0	16	15,04	32,00	92	38,00	4
6945897	W4NBM20009RBT	20,0	20	18,80	38,00	104	50,00	4

WCE4 • Series W4NB • Ball Nose • 4 Flute • Weldon® Shank • Metric






WU20PE




● first choice
○ alternate choice

order #	catalogue #	D1	D	D3	length of cut Ap1 max	length L	L3	Z U
6945884	W4NBM05003RBW	5,0	6	4,70	13,00	57	18,00	4
6945885	W4NBM06003RBW	6,0	6	5,64	13,00	57	21,00	4
6945888	W4NBM08004RBW	8,0	8	7,52	19,00	63	27,00	4
6945889	W4NBM10005RBW	10,0	10	9,40	22,00	72	32,00	4
6945898	W4NBM12006RBW	12,0	12	11,28	26,00	83	30,00	4
6945899	W4NBM16008RBW	16,0	16	15,04	32,00	92	38,00	4
6945900	W4NBM20009RBW	20,0	20	18,80	38,00	104	50,00	4

Application Data • WCE Side Milling • Slotting • Metric

Material Group																				
	Side Milling		Slotting		WU20PE			Recommended feed per tooth (fz = mm/th) for side milling (A). For slotting (B), reduce fz by 20%.												
					Cutting Speed – Vc m/min			D1 – Diameter												
	ap	ae	ap	min	Start	max	mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0	
P	0	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	1	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,4 x D1	1,0 x D1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	3	ap1max	0,4 x D1	1,0 x D1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	4	ap1max	0,4 x D1	0,75 x D1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	5	ap1max	0,4 x D1	1,0 x D1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
M	1	ap1max	0,4 x D1	1,0 x D1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	3	ap1max	0,4 x D1	1,0 x D1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071
K	1	ap1max	0,4 x D1	1,0 x D1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,4 x D1	1,0 x D1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	3	ap1max	0,4 x D1	1,0 x D1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
S	1	ap1max	0,4 x D1	0,3 x D1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,4 x D1	0,3 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061
	3	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	4	ap1max	0,4 x D1	1,0 x D1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084
H	1	ap1max	0,4 x D1	0,75 x D1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	2	ap1max	0,4 x D1	0,5 x D1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071

Application Data • WCE Side Milling • Slotting BN • Metric

Material Group																				
	Side Milling		Slotting		WU20PE			Recommended feed per tooth (fz = mm/th) for side milling (A). For slotting (B), reduce fz by 20%.												
					Cutting Speed – Vc m/min			D1 – Diameter												
	ap	ae	ap	min	Start	max	mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0	
P	0	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	1	ap1max	0,4 x D1	1,0 x D1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,4 x D1	1,0 x D1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	3	ap1max	0,4 x D1	1,0 x D1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	4	ap1max	0,4 x D1	0,75 x D1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	5	ap1max	0,4 x D1	1,0 x D1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
M	1	ap1max	0,4 x D1	1,0 x D1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	3	ap1max	0,4 x D1	1,0 x D1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071
K	1	ap1max	0,4 x D1	1,0 x D1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,4 x D1	1,0 x D1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	3	ap1max	0,4 x D1	1,0 x D1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
S	1	ap1max	0,4 x D1	0,3 x D1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,4 x D1	0,3 x D1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061
	3	ap1max	0,4 x D1	1,0 x D1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	4	ap1max	0,4 x D1	1,0 x D1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084
H	1	ap1max	0,4 x D1	0,75 x D1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	2	ap1max	0,4 x D1	0,5 x D1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071

Application Data • WCE Side Milling • Long • Metric

Material Group	Side Milling		Recommended feed per tooth (fz = mm/z) for side milling. No slotting operations recommended.																
			WU20PE			D1 – Diameter													
			Cutting Speed – Vc m/min			mm	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0	18,0	20,0	25,0	
			ap	ae	min														Start
P	0	ap1max	0,2xD1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	1	ap1max	0,2xD1	150	175	200	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,2xD1	140	165	190	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	3	ap1max	0,2xD1	120	140	160	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	4	ap1max	0,2xD1	90	120	150	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	5	ap1max	0,2xD1	60	80	100	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
M	6	ap1max	0,15xD1	50	65	75	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071
	1	ap1max	0,2xD1	90	100	115	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,2xD1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
K	3	ap1max	0,2xD1	60	65	70	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071
	1	ap1max	0,2xD1	120	135	150	fz	0,021	0,028	0,036	0,044	0,060	0,072	0,083	0,092	0,101	0,108	0,114	0,124
	2	ap1max	0,2xD1	110	125	140	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
S	3	ap1max	0,2xD1	110	120	130	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
	1	ap1max	0,1xD1	50	70	90	fz	0,017	0,023	0,030	0,036	0,050	0,061	0,070	0,079	0,087	0,095	0,101	0,114
	2	ap1max	0,1xD1	25	30	40	fz	0,009	0,013	0,016	0,019	0,026	0,032	0,037	0,042	0,046	0,050	0,054	0,061
	3	ap1max	0,15xD1	60	70	80	fz	0,014	0,019	0,024	0,029	0,040	0,048	0,056	0,063	0,070	0,076	0,081	0,091
H	4	ap1max	0,15xD1	50	55	60	fz	0,011	0,016	0,021	0,026	0,037	0,045	0,052	0,058	0,064	0,069	0,074	0,084
	1	ap1max	0,15xD1	80	110	140	fz	0,016	0,021	0,027	0,033	0,045	0,054	0,062	0,070	0,077	0,083	0,088	0,098
	2	ap1max	0,15xD1	70	90	120	fz	0,012	0,016	0,020	0,025	0,034	0,040	0,047	0,052	0,057	0,061	0,065	0,071

WCE • Adjustment Factor Table for Feed Calculation

To calculate application-specific cutting data, please use KV coefficient table to the right for adaptation of cutting speed and KFz for feed, respectively.

Vc new = Vc * Kv
Fz new = IPT * KFz

Calculation example:
Application: D = 20mm; M2 material group;
Ae = 2mm
Cutting data recommendation: Vc = 80 m/min;
fz = 0,089 mm/th
Adjustment coefficients: Ae = 2mm equals 10,0%;
Kv = 1,35; KFz = 1,7

Final cutting data recommendation:
Vc new = 80 * 1,35 = 108 m/min
Fz new = 0,089 * 1,7 = 0,15 mm/min

Metric

	Ae/D	2%	4%	5%	8%	10%	20%	30%	40%	50%
Speed factor	Kv	2	1,5	1,45	1,4	1,35	1,25	1,2	1	1
Feed factor	KFz	2,4	2,3	2,2	2	1,7	1,25	1,02	1	1

Inch

	Ae/D	2%	4%	5%	8%	10%	20%	30%	40%	50%
Speed factor	Kv	2	1.5	1.45	1.4	1.35	1.25	1.2	1	1
Feed factor	KFz	2.4	2.3	2.2	2	1.7	1.25	1.02	1	1

WCE 4-FLUTE END MILL

VERSATILE SOLID CARBIDE END MILLS

WORLD HEADQUARTERS

WIDIA

Kennametal Inc.
1600 Technology Way
Latrobe, PA 15650 USA
Tel: 1 800 979 4342
w-na.service@widia.com

EUROPEAN HEADQUARTERS

WIDIA

Kennametal Europe GmbH
Rheingoldstrasse 50
CH 8212 Neuhausen am Rheinfall
Switzerland
Tel: +41 52 6750 100
w-ch.service@widia.com

ASIA-PACIFIC HEADQUARTERS

WIDIA

Kennametal (Singapore) Pte. Ltd.
3A International Business Park
Unit #01-02/03/05, ICON@IBP
Singapore 609935
Tel: +65 6265 9222
w-sg.service@widia.com

INDIA HEADQUARTERS

WIDIA

REGD OFFICE: WIDIA India Tooling Pvt Ltd
CIN: U28110KA2018PTC119396
Survey No 11 Nagasandra
Adjacent to Nagasandra Metro Station
Bengaluru - Pune National Highway
Bengaluru - 560073 India
Tel: +91 80 2839 4321
w-in.service@widia.com



TOOLING & MACHINERY

COMPLETE METALWORKING SOLUTIONS

(800) 991-4225

www.ahbinc.com

ISO Certified

customerservice@ahbinc.com

