



AHB Waylubes

ISO 32, 68, 100, 220

PRODUCT DESCRIPTION

AHB WAYLUBES are formulated to lubricate beds and way tables on a variety of machines. These products have excellent adhesion and high film strength along with a superb resistance to oxidation. **AHB WAYLUBES** are designed specifically to provide excellent lubricity for slide ways of all machine types, providing uninterrupted operation.

BENEFITS

- Inhibits rust, corrosion, and oxidation
- Reduces wear rates
- Excellent coolant compatibility
- Reduces stick-slip chatter
- High degree of lubricity
- Compatible with surface metallurgy
- Resists emulsification with coolants

APPLICATIONS

- Slides and ways on machines

PROPERTIES

ISO GRADE	32	68	100	220
Viscosity @ 40°C, cST	30 - 34	66 - 70	95 - 105	215 - 225
Viscosity @100°C, cST	5 - 6	10 - 11	13 - 14	18 - 19
Viscosity Index	107	136	125	94
API Gravity	0.91	0.91	0.91	0.91
Flash Point, min °C	230	255	255	255
Pour Point, min °C	-20	-20	-10	-10
Rust Protection	Pass	Pass	Pass	Pass

STORAGE

AHB WAYLUBES should be stored away from extreme heat and cold. Do not cut or weld on or near empty containers.

HEALTH & SAFETY

AHB WAYLUBES contain no ingredients currently recognizes by I.R.A.C. or O.S.H.A. Good industrial hygiene practices should be followed when using this or any other industrial products.

PACKAGING

AHB WAYLUBES are available in 5 gallon pails, 55 gallon drums, and 330 gallon totes.