



Use CECOR's CE10 Combination Electric Sumpcleaner/Filter and Coolant Dispenser anywhere in the plant. Unit plugs into any standard electrical outlet.

- Available in 60/60, 100/100, 150/150, 200/200, 250/250 and 300/300 gallon capacity.
- Two separate tanks on a single chassis.
- Pumping rate to 60 gallons per minute.
- Generates suction to 17" Hg (Mercury) or 231" water.
- 115/60/1 electricals
- Efficient 1 Horsepower electric motor

CE10-100/100PT

Caution: Machines must not be used for flammable fluids (fuels, paints, solvents, etc.) . Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc.)



Standard F10 Filter

F10 - 1.0 Cubic Foot Filter

The F10 strainer basket and fabric liner has a capacity of 1.0 cubic foot and is standard on the CE10. The reusable filter has built in grips and is small enough for one person to lift. Coarse, fine and polypropylene filter bags come standard with the F10 basket.



Optional F23 Filter

F23 - 2.3 Cubic Foot Filter (Optional)

With a 2.3 cubic foot capacity, the F23 filter is fitted for fork lift or hook hoist handling. Patented compound linkage and rotary latch controls the bottom opening door for safe emptying. The filter assembly comes complete with a polypropylene filter sleeve. The F23 filter is optional on the CE10. Optional fine weave polypropylene filter sleeve available.



- Pumping Rate:** Up to 60 gallons per minute.
- Suction Lift:** 17" Hg (Mercury) or 231" water.
- Pressure Discharge:** 6 PSI (pounds per square inch) with safety backup valve.
- Filter:** F10 Filter has 1 cu. ft. capacity and is standard on the CE10. Optional F23 (2.3 cu. ft.) capacity is recommended when coolant is loaded with chips and swarf.
- Spill Prevention:** Automatic overflow protection. All discharge ports valved.
- Hose:** 1-1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect couplers and suction tools.
- Cleaning Tools:** Flared Nozzle
Flexible Nozzle
Straight Nozzle
- Power Cord:** 15 feet standard
50 feet available

CE10-100/100PT Sumpcleaner/Filter

Tank Size: 60/60, 100/100, 150/150, 200/200, 250/250 and 300/300 gallon capacity.

Motor: 1 HP Electric Motor
Volts 115
Amps 13.4
Hertz 60
Phase 1

Pump: Rotary, vane-type vacuum pump

See page 33 for information on base options

Options

Model Number	Tank Size	Cleanout Door	Transport	Wheels	Dimensions	Shipping Weight	TW Base	PLD Base	PKM Base	CB1 Base	CB2 Base	CB3 Base	CB4 Base	CB5 Base	F23 Filter	Floor Squeegee		
CE10-60/60PT	60 gallons per side	8" x 10" with a 1 1/4" drain port	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	86" long 30" wide 48" high	734 lbs.	X	X	X	X	X	X	X	X	X	X		
CE10-100/100PT	100 gallons per side				92" long 34" wide 54" high	980 lbs.	X	NA	X	X	X	X	X	X	X	X	X	X
CE10-150/150TW	150 gallons per side	16" diameter hinged door with a 2 1/2" drain port.	TW Base- Tow Bar with pintle-eye hitch to accommodate most in-plant tugs or tractors.	Two heavy-duty 16" x 4" wheels and one 12" x 3" swivel casters.	96" long 40" wide 62" high	1230 lbs.	S	NA	X	X	X	X	X	X	X	X		
CE10-200/200TW	200 gallons per side				Two 16" x 4" wheels and two 12" x 3" swivel casters.	99" long 46" wide 68" high	1665 lbs.	S	NA	X	X	X	X	X	X	X	X	X
CE10-250/250TW	250 gallons per side				Two heavy-duty 16" x 5" wheels and two 12" x 3" swivel casters.	111" long 48" wide 70" high	1750 lbs.	S	NA	X	X	X	X	X	X	X	X	X
CE10-300/300CB1	300 gallons per side		CB1 Base - Custom base for mounting on trailer or truck.	Not applicable.	121" long 42" wide 60" high	1863 lbs.	NA	NA	NA	X	X	X	X	X	X	X		

NOTE: Engineering specifications subject to change without notice.

X = Available
S = Standard
NA = Not Available