



Rust Preventative

Signature Collection

■ Emulsifiable Oils ■ Solvent Based ■ Straight Oils ■ Synthetics

Synthetics

PRODUCT	METALS PROTECTED	TYPE OF FILM	PROTECTION LENGTH	FLASH POINT	DILUTABLE	NITRITE	AMINE	AZOLE
DuBois 104SW	Ferrous	Imperceptible	1 -2 months	None	Y		Y	Y
GX Proof 6151Y	All	Imperceptible	1 - 6 months	None	Y		Y	Y
GX Proof 1293	Ferrous	Imperceptible	1 - 6 months	None	Y	Y	Y	Y
Rust Prevent 910	All	Imperceptible	1 - 3 months	None	Y	Y		Y
Rust Prevent SYN 3-X	All	Imperceptible	1 - 30 days	None	Y		Y	Y

Emulsifiable Oil

PRODUCT	METALS PROTECTED	TYPE OF FILM	PROTECTION LENGTH	FLASH POINT	DILUTABLE	AMINE
Lab Oil 100	All	Oily	3-6 months	None	Y	
Lab Oil 100WT	All	Oily	3-6 months	None	Y	Y
Perkote 10-985	All	Oily	3 - 6 months	348°F	Y	
Rust Prevent 100	All	Oily	3 - 6 months	250°F	Y	

Solvent Based

PRODUCT	METALS PROTECTED	TYPE OF FILM	PROTECTION LENGTH	FLASH POINT	DILUTABLE	BARIUM	CALCIUM
CimGaurd® Oak Protect® 408	All	Waxy	2 years	120	N	Y	
CimGaurd® Oak Protect® 2405	All	Oily	2 years	124	N	Y	
GX Proof 8140	All	Oily	1 year	145	N		
Pen Dip 300	All	Oily	1 year	145	N		Y
Pen Dip A	All	Dry Waxy	1 year	145	N		Y
Perkote 30-266	All	Dry Waxy	1 year	125	N	Y	
Perkote 30-268-HC	All	Dry Waxy	1 year	145	N		Y

Straight Oil

PRODUCT	METALS PROTECTED	TYPE OF FILM	PROTECTION LENGTH	FLASH POINT	DILUTABLE	BARIUM	CALCIUM
Perkote 40-315-B	Ferrous	Oily	2 years	270	N	Y	
Perkote 80-875	All	Oily	1 year	400	N	Y	
Perkote 80-325	All	Oily	1 year	320	N		Y

AHB

TOOLING & MACHINERY

COMPLETE METALWORKING SOLUTIONS

(800) 991-4225

www.ahbinc.com

ISO Certified

customerservice@ahbinc.com