

Dynaflux R1100G

Cooling System with Rotary-GEAR Pump "G"

IN-STOCK READY TO SHIP

- Factory set at 50 psi adjustable to 80 psi
- 3 gallon reservoir
- 115 or 230 VAC / 1 ph - 50 / 60 Hz
- 5.6 / 2.8 amp: 60 Hz
- 15,000 BTU
- Dimensions: 23"L x 11"W x 14.75"H
- 1/4" FPT (water in/out) with 5/8" LH standard inert gas fitting
- 8' power cord
- Rugged polyethylene non-dent construction
- Visible water level through tank
- Thermal overload
- Net weight: 42 lbs / 19 kg
- Foam packed for UPS shipment

R1100 G: Rotary GEAR Pump

- 1.8 gpm at 50 psi
- Built in by-pass to tank

DEFENSE Anti-Freeze and Pump Lubricant

Provides year round protection for Dynaflux water coolers and other closed loop systems.

- PART NO. 927: Ready-to-use (No dilution needed).
- PART NO. 929: Concentrate to be diluted with distilled water.
- PART NO. 947: Ready-to-use propylene glycol.



DYNAFLUX
WATER CHILLER

WR1100G

DYNAFLUX
QUALITY PRODUCTS



LEARN MORE: www.wsiweld.com/depot



www.wsiweld.com · 844-974-9353
salesteam@wsiweld.com · +1-216-475-5629

DISTRIBUTED BY:



Monday - Friday 7:30 am - 5:00 pm EST

Customer Service: 800-991-4225

www.ahbinc.com

customerservice@ahbinc.com