

Tramp Oil Removal

Model: OS4-801-P-P

The Ebbco Oil Slick has been designed to Remove Free And Mechanically Emulsified Tramp Oils From Machine Tool Coolants Used In CNC Machining Centers, Lathes And Aqueous Parts Washer. This Compact Filtration System Is Easy To Install On Existing Equipment And Will Remove Suspended Solids, Giving You Consistent Part Quality, Increase Tool Life And Extend Fluid Life. This System Is Designed To Run Continuous And Unattended.

By Using A Ebbco's Unique Skimmer Assembly Tramp Oil Is Suctioned Off Of The Top Of The Tank To The separation chamber filled with coalescing balls,, There Oil Is Extracted Out And Discharged Into A 3.5 Gallon Receptacle. Clean Fluid Is Then Polished Through a Micron Rated Filter Cartridge and Returned To The Sump.

Specifications:

Flow Rate	4 GPM
System Inlet	Floating Skimmer Magnetic Skimmer- Optional
System Outlet	1" Hose
System Pump	Air Operated Double Diaphragm
System Voltage	N/A
Filter Vessel	HSL-20
Replacement Cartridge	(2) PMF-801-C
Maximum Operating Temp	140°F
Base	Compact Portable
Operating Pressure	50 PSI Max

