MistBuster® 2000 - Next Generation

Model	MB2000
Airflow	Variable to 1650 cfm @ .6" W.C.
Cabinet	16 gauge steel cabinet with powder coated chemical resistant baked enamel, available in ivory or gray textured finish
Power Input	115 Vac, 60 Hz, 1 ph, 4 amps 240 Vac, 60 Hz, 1 ph, 2 amps
Efficiency	Ultimate efficiency up to 99.6% on all submicron particles as measured by independent lab test in accordance with ASHRAE standard 52.2 at 1000 CFM.
Filtration	1st Stage: 4" aluminum mesh impinger
Stages	2nd Stage: DuroClean (Long Life) Electronic Cell x 2
	3rd Stage: MistBuster (High-Efficiency) Cell x 2
	4th Stage: Optional MistBuster (High-Efficiency) Cell x 2
	5th Stage: Optional HEPA filter 99.97% efficiency, ESF Filter, or Carbon Module
Features	Two self-regulating, dual voltage solid state power supply (standard)
	Patented water/oil coolant collector selector
	Backward curved, vibration-free, direct drive motorized impeller rated at 1950 cfm maximum
	Ten-foot power cord with molded plug
Dimensions	Cabinet: 26.00"L x 26.30"W x33.06"H
Inlet Opening	16" x 20.75"
Weight	203 lbs installed; 230 lbs shipping
Accessories	Machine Mount Stand Pedestal Stand Ceiling Mount Kit Wall Mount Kit Plenum Diffuser HEPA Postfilter ESF Postfilter Carbon Module

Specifications subject to change without notice.



COMPLETE METALWORKING SOLUTIONS
(800) 991-4225 www.ahbinc.com
ISO Certified customerservice@ahbinc.com



coolant selector





