





Cold Saw Advantage



Sample of virtually "burr-free" cutting.



Clearly marked scale to help the operator set-up angle cuts with preset stops at 45° R, 45° L and 0° on manual, pneumatic vise, and semi-automatic models, 45° R, 15° L and 0° on automatic models.



KSA64 5' x 12" wide roller stock table, (KSA63 10' x 12" wide roller stock table also available).



CS9052 foot pedal with cord for KALAMAZOO semi-automatic and automatic models (FS or FA350SA)



P12 Adjustable Stock Stand. adjustment range from 37" to 46" high.



Spray mist coolant unit for FA350A SA and FA350A models. Smaller spray mist coolant units furnished with CA350 and CA350PV. Flood coolant system furnished on all steel cutting machines.

Optional Equipment (CA, CS, FS, FA models only)

Part No.	Description	Part No.	Description
CS7000	Adjustable Stock Stop	CS9001 B	230V Vacuum Chip Removal System (1300 cfm)
CS7401	Aluminum, 90 degree Vise Wear Plate (4 required)	CS9001C	440V Vacuum Chip Removal System (1300 cfm)
CS7401S	Steel 90 degree Vise Wear Plate (4 required)	CS9052	Foot Pedal Option for SA and Auto Models
CS7404	Diamond Shape Wear Plates for CA & FA Models	P12	Adjustable Stock Stand (37"-46")
CS7404S	Diamond Shape Wear Plates for CS & FS Models	KSA64	5 Foot Roller Stock Table 12" wide
CS7450	Speed Change Kit (1700 rpm) CA & FA Machines	KSA63	10 Foot Roller Stock Table 12 " wide
CS7451	Speed Change Kit (3400 rpm) CA & FA Machines	RTS07	Adjustable Stock Stop for Roller Stock Table
CS7452	Speed Change Kit (20/40 rpm) CS & FS Models	CS6336	Overhead Roller Assembly
CS7453	Speed Change Kit (30/60 rpm) CS & FS Models	CS7300A	Variable Vise Pressure (PV, SA)
CS7500	Powered Overhead Clamp Assembly (Bundle Cutting)	CS7300B	Variable Feed Pressure (SA)
CS7600	Fixture Mounting Table Assembly	CS7300C	Dual Variable Clamp Pressure (A)
CS9001A	208V Vacuum Chip Removal System (1300 cfm)	CS7300D	Variable Head/Vise Pressure (SA)
		CS7300E	Variable Head/Vise Pressure (A)