

Clausing Kalamazoo Vertical Bandsaws

Features:

- 230v/460v/60/3 Electricals
- Magnetic Starter with 110v Control Circuit and Overload Protection
- 3 Hp (2.2Kw) TEFC Motor
- Dual Range Transmission
- 1/2" (13mm) and 3/4" (19mm) Chevron type Blade Guides with Back-Up Roller
- Fixed Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R)
- Hydraulic Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top Table Travel 13"
- Bonded Rubber Band Wheels
- 110v Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 3/4" (19mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) year limited warranty

Specifications:

Model	V2012F	V2012H	V2812F	V2812H
Throat	20" (508mm)	20" (508mm)	28" (710mm)	28" (710mm)
Work Height	12.75" (325mm)	12.75" (325mm)	12" (305mm)	12" (305mm)
Drive Motor	3 Hp (2.2Kw)	3 Hp (2.2Kw)	3 Hp (2.2Kw)	3 Hp (2.2Kw)
Blade Length	159"-162" (4040-4115mm)	159"-162" (4040-4115mm)	197"-199" (5004-5055mm)	197"-199" (5004-5055mm)
Blade Width	1/8"-1" (3-25mm)	1/8"-1" (3-25mm)	1/8"-1" (3-25mm)	1/8"-1" (3-25mm)
Blade Speed (fpm)	50-5200	50-5200	50-5200	50-5200
Dimensions				
Length	51" (1295mm)	51" (1295mm)	61" (1550mm)	61" (1550mm)
Width	41" (1040mm)	44" (1117mm)	41" (1040mm)	44" (1117mm)
Height	81" (2057mm)	81" (2057mm)	91" (2311mm)	91" (2311mm)
Net Weight	1,390 lbs. (630 kg)	1,500 lbs. (680 kg)	1,650 lbs. (748 kg)	1,760 lbs. (798 kg)
Shipping Weight	1,540 lbs. (698 kg)	1,650 lbs. (748 kg)	1,800 lbs. (816kg)	1,900 lbs. (861 kg)

All specifications subject to change without notice or obligation.

Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts

