



724 Robbins Road Phone 616-842-7110 800-937-3253  
 Grand Haven, Michigan 49417 Fax 616-842-0859 800-846-3253  
 Web: [www.dakecorp.com](http://www.dakecorp.com) E-mail : [customerservice@dakecorp.com](mailto:customerservice@dakecorp.com)



**SPECIFICATIONS**

Machine Type	Gravity feed, rolling frame vertical bandsaw
Cut Capacity	9 inches x 14-½ inches
Blade (frame) Travel	9 inches
Frame Travel	Gravity counter balance weight with hydraulic regulation
Maximum work height	14-½ inches
Blade Width/Length	¼ - ¾ inches / 120 inches
Blade Speeds (Feet per Minute)	70 / 140 / 270 / 540 FPM
Worktable Dimensions	29 inches x 18 inches
Mitering	45°
Worktable Height from Floor	36-½ inches
Band Wheels	14 inch diameter
Horsepower	1 H.P.
Weight	810 pounds
Overall Height	66 inches
Base Width	29 inches
Depth	40 inches
Voltage	<ul style="list-style-type: none"> <li>• Available 120-volt single phase</li> <li>• Available 230-volt single phase</li> <li>• Available 230-volt three phase</li> <li>• Available 460-volt three phase</li> </ul> <b>Machine should be wired to main service by a qualified Electrician.</b>
AMP	<ul style="list-style-type: none"> <li>• 20-amp service for 120-volt &amp; 230-volt machines</li> <li>• 16-amp service for 460-volt machine</li> </ul>
Operating Temperature	No special operating temperature level

## OPTIONS

Part Number	Description	
716725	Heavy Duty Locking Caster	

## FEATURES

- Roller blade guides, miter gauge with C-Clamp assembly, headlock, cutting chart, and one standard blade furnished with the machine.
- Large precision ground table for large work surface.
- Heavy-duty gear box with 4 speed step pulleys for fast speed changes.
- 14" lipped band wheels with rubber tires for smooth operation and long life.
- Blade changes are made quickly with easy access to the band wheels.
- Welded steel base and head frame that is rigid, heavy and durable that helps reduce any wobble and vibration.
- Adjustable counterweight and infinitely variable hydraulic feed pressure regulation, for hands free cutting of most materials.
- Front mounted hydraulic feed control for operator convenience and operation.
- Electrical package that includes low voltage controls, low voltage coil and E-stop button.
- Heavy cast miter gauge and C-Clamp for holding material during the cutting operation, whether it is straight or miter cutting.
- Head lock allows you to lock the head frame in a stationary position for operating the saw as a vertical bandsaw for scroll, contour cutting or ripping.
- Made in the U.S.A.