



Notching saw AKS 134/00

- > Variable notching possibilities for mullion and transom combinations for e.g. curtain walls, wintergarden, skylights and special designs
- > Only the sawing units move while the workpiece remains fixed, thus providing precise and safe notching
- > Both saw units can be simultaneously adjusted in height by means of a hand wheel (analogue display on the hand wheel)
- > Indication of the cutting depth analogue display
- > Manual adjustment of the cutting angles with digital display of the tilting angles
- > Support table with cross slide and pivoting back fence is manually adjustable for optimum use of the cutting range
- > Pivoting angle indication of the back fence by digital display
- > Horizontal and vertical profile material clamping
- > Automatic working cycle at 90° angle (2-hand control when cutting special angles)
- > Hydro-pneumatic saw feed

Technical information

Saw unit lower (vertical):

- > Saw blade diameter 550 mm
- > Tilting range 45° from the front up to + 60° to the rear
- > Cutting depth 210 mm max.
- > Power supply 230/400 V, 3~, 50 Hz
- > Power output 3 kW with motor brake
- > Spindle speed 2.800 r.p.m.
- > Angle adjustment for tilting range manual with digital display (standard)

Saw unit upper (horizontal):

- > Saw blade diameter 500 mm
- > Tilting range from 55° to the bottom up to 60° to the top
- > Notching depth 190 mm max.
- > Power supply 230/400 V, 3~, 50 Hz
- > Power output 3 kW with motor brake
- > Spindle speed 2.800 r.p.m.
- > Angle adjustment for tilting range manual with digital display (standard)





- Saw feed:
> Stroke 830 mm max.
- Support table:
> Pivoting range from 30° left to 30° right
> Pivoting range manual with digital display (standard)
- > Compressed air supply 7 bar
> Air consumption per working cycle 35 l without mist spray, 45 l with mist spray
> Length 3000 mm, width 1420 mm, height 1600 mm, weight 1250 kg

Optional

- > Laser indication for cutting line
> Support extension with back fence
> Roller support MST
> Saw blades
> High performance cutting fluid

Notching saw AKS 134/10

- > See AKS 134/00, however:
> Equipped with a 4-axis control for automatic adjustment of the horizontal and vertical saw blades for angle cutting, as well as for height adjustment and notching depth
> The input of the values is made via the keyboard



For further information please contact:

- >elumatec GmbH | Pinacher Straße 61 | D 75417 Mühlacker
>Tel. +49 (0)7041 14-266 | Fax +49 (0)7041 14-282 | sales@elumatec.de

The right to make alterations is reserved