



Mitre saw MGS 105

The universal saw for special applications

- > The reliable elumatec principle „Cutting from underneath“:
- > Free access for optimum loading and unloading of profiles
- > The patented saw arm suspension creates a cutting pressure towards the back fence which provides safe clamping of the workpiece
- > Automatically opening safety of hood
- > Pulsed coolant system
- > Standard equipped with saw blade

Technical information

- > Pivoting range manual, to the left and to the right up to 22.5° with digital display E 111
- > Tilting range pneumatic from 90° to 45°
- > Cutting capacity see cutting diagram
- > Saw blade diameter 420 mm
- > Spindle speed 2800 r.p.m.
- > Power supply 230/400 V, 3~, 50 Hz
- > Power output 4 kW
- > Compressed air supply 7 bar
- > Air consumption per working cycle 20 l without mist spray, 32 l with mist spray
- > Length 1400 mm, width 1500 mm, height 1880 mm, weight 750 kg

Optional

- > Hydro-pneumatic saw feed
- > Extraction system
- > Length stop and measuring systems
- > Roller conveyors
- > Saw blades
- > High performance cutting fluid

For further information please contact:

- > elumatec GmbH | Pinacher Straße 61 | D 75417 Mühlacker
- > Tel. +49 (0)7041 14-266 | Fax +49 (0)7041 14-282 | sales@elumatec.de

The right to make alterations is reserved

