CE40MR3 Angle Roll

Manual Angle Roll • Section Bender





Two-Speed Gear Box

- 1 Torque or fine adjustment
- 2 Rapid or coarse adjustment



Manual Center Roll Positioning

ERCOLIN

FEATURES

Universal tooling set forged with smooth surface included with each machine

Vertical or Horizontal Operating Position

- Forged roll shafts precision ground and fitted for maximum performance and minimal deflection
- Roll shafts supported with conical steel bearings on each side of A Frame
- Heavy duty structure and rigid components for high section modulus ratings
- Reinforced engineered mainframe design proven to outperform competitive models
- In-line direct drive roll shaft system 3-roll driven

- Threaded roll shafts with micrometric flange adjustment helps eliminate spacer usage
- Touchpad controls with digital center roll positioning
- Control tower with low voltage controls and foot pedal
- 2-speed gear box with torque multiplier for positioning center roll
- Optional anti-twist correction system required for angle iron "Leg In" applications

CE40MR3 Capacities & Specifications

Pipe (Max.)	2" Sch. 40
Angle (Max.)	2" x 2" x 1/4"
Tube (Max.)	2½" – .125 wall
Roll Shaft Diameter	40mm
Center Roll Positioning	Manual with patented torque multiplier
Shaft Speed	10 RPM
Universal Tooling (Included)	65/8" O.D.
Programming	Not available
Distance between Shafts	105%"
Operating Voltage	220V or 480V 3ph
Length, Width, Height	39" x 26" x 59"
Weight	763 lbs.

All capacities based on mild grade materials; heavy wall and high tensile materials reduce machine capacity.

POPULAR ACCESSORIES



Spray Lubricant



Pipe & Tube Tooling



Anti-Twist Device



Small Radius Tooling

bobkeenan/Bigstock.com



Radius & Degree Measuring Kit

Tooling Sets Pages 62-64

Tooling and Accessories Pages 64-68



Ercolina Bending Application

AHB

TOOLING & MACHINERY, INC.

COMPLETE METALWORKING SOLUTIONS (800) 991-4225 www.ahbinc.com ISO Certified customerservice@ahbinc.com