

MACHINE SPECIFICATIONS

Capacity

Weight Capacity Blade Speed Range Blade Size Blade Guides Blade Tension Bandwheel Size Vise Sawing Force Blade Drive Hydraulic Drive Work Height Coolant Capacity Hydraulic Capacity Shipping Weight Machine Dimensions

@ 90° 16" H x 20" W, Round 16" @ 45° 16" H x 10" W, Round 10" 5.000 lbs 60-425 SFPM 1¼ " x .042" x 15' Rollers and Carbide Side Blocks Manual with Indicator 20" Manual 30-120 lbs 71/2 HP, 3ph 1/₃ HP Motor 26" 15 Gallons ³∕₄ Gallon 2.100 lbs 49" L x 97" W x 83" H

STANDARD EQUIPMENT

1¹/₄" Bimetal Blade **Rollers and Carbide Side Blocks** Semi-Automatic Operation **Built-In Coolant System Console Controlled Blade Speed** Blade Powered Rotary Cleaning Brush 7¹/₂ HP AC Vector Drive Fused Disconnect with Lockout NFPA-79 Electrics Automatic End-of-Cut Shut Down Quick and Easy Blade Speed Change Blade Speed and Work Selector Chart Feed Pressure Monitor/Regulator All Safety Guards with Door Interlocks Operator Manual and Parts List Factory Trained Start-Up Instructions

*Specifications Subject to Change Without Notice

W.F. Wells, Inc.

16645 Heimbach Road • Three Rivers, MI 49093 Phone: (269) 279-5123 • Fax: (269) 279-6337 Web page: www.wfwells.com • E-mail: info@wfwells.com