



Model F-16-3 Heavy Duty Horizontal Band Cut-Off Machine





MADE IN THE USA

The F-16-3 series features automatic preset hydraulic blade tension, a hydraulic vise with variable clamping pressure and increased sawing pressure for severe applications. These features ensure easier and more productive operator control.

## **MACHINE SPECIFICATIONS**

Capacity @ 90° Weight Capacity Blade Speed Range Blade Size Blade Guides Blade Tension Bandwheel Size Vise Sawing Pressure **Blade Drive** Hydraulic Drive Work Height Coolant Capacity Hydraulic Capacity Shipping Weight Machine Dimensions

Rectangular 17" H x 20" W, Round 17" 5.000 lbs. 60-500 SFPM 1½" x .050" x 16'8" Carbide with Roller Backup Hydraulic 22" Full Stroke, Hydraulic 0-500 lbs. 10 HP, AC Vector Drive 2 HP Motor 35" 10 Gallons 20 Gallons 3,200 lbs. 101" L x 48" W x 88" H

## **STANDARD EQUIPMENT**

1<sup>1</sup>/<sub>2</sub>" Bimetal Blade Carbide Guides with Backup Rollers Hydraulic Vise with Variable Pressure Hydraulic Blade Tension Semi-automatic Operation **Built-in Coolant System Console Controlled Blade Speed** Blade Powered Rotary Cleaning Brush 10 HP AC Vector Drive Fused Disconnect with Lockout NFPA-79 Electrics Automatic End-of-Cut Shut Down Quick and Easy Blade Speed Change Blade Speed and Work Selector Chart Feed Pressure Monitor/Regulator All Safety Guards with Door Interlocks **Operator Manual and Parts List** Factory Trained Start-Up Instructions

\*Specifications Subject to Change Without Notice

W.F. Wells, Inc. 16645 Heimbach Road • Three Rivers, MI 49093 Phone: (800) 991-4225 Web page: www.wfwells.com • E-mail: customerservice@ahbinc.com