Rugged Powerful Accurate In Production Since 1933

Manual Bandsaw





Model 1016 Manual Bandsaw



Standard Features

Spring-Loaded Carbide Guides with Rollers

Combination Reduction Gearbox and Perimeter Ring Gear Blade Drive

2hp Baldor® Motor

Four Blade Speeds

Rite-Tension® Band Tensioning Device

Variable Hydraulic Downfeed Control

Flood Type Wet Cutting System

Rotary Blade Brush

110 Volts at Controls

Overload and Undervoltage Protection

Precision Ground Bed

Quick Acting Vise

Positive Frame Lock

Adjustable Stock Stop/Back-Gauge

Auto Shut-Off at End of Cut

OSHA Blade Guarding

Tiger-Tooth® Bi-Metal Blade

Coolant for Initial Start-Up

Specifications

 Capacity

 Round
 10.5"

 Flat
 16.5"

 Rectangular
 10" x 16"

 45° Angle
 10" x 9"

Blade Size 1" x .035" x 11'6" (138") Blade Speeds 50-100-175-275 SFPM

Blade Guides Carbide Guides with Rollers

Blade Tension Manual Rite-Tension®
Electrical Options 115-208-230/60/1 or

208-230-460/60/3

Coolant System Tank Capacity 8 Gallons
Submersible Pump 115V/

.6 Amp/170 GPH

Vise Control Quick Acting/Manual Screw

Swivel Vise To 45°

Feed Control Variable Hydraulic with

Counterbalance Spring

Band Wheels 15" Diameter Cast Iron

Bed Height 29"

Floor Area 40"W x 84"L

Shipping Weight 900 Lbs.

Available Factory Installed Options

Variable Speed Blade Drive (70-375 SFPM)

Casters (Set of 4, 2 Locking)

NFPA Electrics (with Disconnect)

Working Light with Transformer

Stock Stand, 18"

5' Non-Powered Roller Conveyor

10' Non-Powered Conveyors



COMPLETE METALWORKING SOLUTIONS

(800) 991-4225 ISO Certified www.ahbinc.com customerservice@ahbinc.com

