20" Throat with 16" or 24" Under the Guide





8538 Wellsaw V20_V20-24 Vertical Bandsaw4 | 7.1.09 | jeff@allied-art.com



Manufactured in the United States of America





Standard Features

Heavy Tube Steel Frame
Precision Ground Cast Iron Table with Replaceable Throat Plate
Unique Heavy Duty Roller Guides
Rotate 90° to Accommodate Long Materials
Baldor® Motor
Magnetic Starter with Undervoltage and Overload Protection
115 Volts at Controls
Two Speed Cast Iron Gearbox with Helical Gears and Oil Bath Lubrication for Quiet Operation
Blade Speed Indicator
Blade Tension Indicator
Flexible Arm Worklight
Chip Blower (Shop Air)
Removable Chip Tray
Tiger-Tooth® Bi-Metal Blade
OSHA Blade Guarding
Rotary Blade Brush

Specifications

Capacity Throat Table to Guide V-20-24	20" Deep 16" High 24" High
Blade Size Standard Optional	3/16" through 3/4" 1/2" through 1" (This Option Not Available on V-20-24)
Blade Length V-20-24	14'9" (177") 16'1" (193")
Band Wheels	21" Cast Aluminum with Replacable Rubber Tires
Blade Speeds Low Range High Range	45-400 SFPM 325-3000 SFPM
Blade Guides	Sealed Ball Bearings with 90° Rotation Feature
Table Size Tilt Height	26" x 26" Cast Iron 5° Inside and 45° Outside 37-1/2"
Drive Motor Three Phase Single Phase	3hp 208/230/460 Volt 115/208/230 Volt
Floor Area Height Standard V-20-24	32" Wide x 48" Deep 83-1/2" 91-1/2"
Shipping Weight Standard V-20-24	950 Lbs. 1050 Lbs.

Available Factory Installed Options

Ideal® Blade Welder, Grinder and Shear

24" Extended Height (Model V20-24)

Miter Gauge

Rip Fence, 26"

1" Blade (Not Available on V-20-24)

Vector AC Drive Variable Bandspeed Now Standard

Spray Mist Coolant System

Vacuum Nozzle

Extension Table

Stock Stand

5' and 10' Non-Powered Roller Conveyor

J.I.C. or NFPA Electrics (with Fused Disconnect)

Consult Factory for Additional Options

8538 Wellsaw V20_V20-24 Vertical Bandsaw4 | 7.1.09 | jeff@allied-art.com



TOOLING & MACHINERY

(800) 991-4225

ISO Certified

COMPLETE METALWORKING SOLUTIONS

www.ahbinc.com

customerservice@ahbinc.com