FREE CUTTER BODY



RECEIVE A FREE CUTTER BODY WITH THE PURCHASE OF 40 INSERTS





PROMO CODE: PROMO-FCUT

Cutter Dia.					Р		М	K	N
in	mm	Insert Model	ар	Nose Radius	ACP200 ACP300		ACM300F	ACZ310	DS20
					Prehardened Steel	General Steel	Stainless Steel	Cast Iron	Aluminum
.500625 12	12-17	ARG160902	.354	.008	_	0	0	0	0
	12-17	ARG160904	.354	.016	0	0	0	0	0
.750	20-21	ARG200902	.354	.008	_	0	0	0	0
		ARG200904		.016	0	0	0	0	0
1.000 25-26	25.27	ARG250902	25/	.008	_	0	0	0	0
	23-26	ARG250904	.354	.016	0	0	0	0	0
1.250	32-33	ARG321102	.433	.008	_	0	0	0	0
		ARG321104		.016	0	0	0	0	0
1 500 2 000	40-50	ARG401102	.433	.008	_	0	0	0	0
1.500-2.000		ARG401104		.016	0	0	0	0	0



Cutter Dia.			Effective Cutting Length (ap)	Nose Radius	Р	М	К	N
Cutter Dia.		Insert Model			ACP300	ACM300F	ACZ310	DS20
in	mm		3 (24)		General Steel	Stainless Steel	Cast Iron	Aluminum
.625	16-17	BRG160808			0	0	0	0
.750	20-21	BRG200808	.315	.031	0	0	0	0
1.000	25-26	BRG250808			0	0	0	0
1.250 32-33	22.22	BRG321008	.394	.031	0	0	0	0
	3∠-33	BRG321032		.125	_	_	_	0

- Must purchase 40 of the same insert to receive the free cutter body
- Free cutter body includes all standard FULLCUT catalog items
- Inserts are available in packages of 10 pcs.
- SE (sharp edge) type prevents burrs; recommended for stainless steel & mild steel

FREE CUTTER BODY TYPES







Low-resistance, high-efficiency cutter especially for cross-feed machining. For grooving & shoulder milling.

Ad= Integral body with dual contact .35" system, Fullcut Mill Ø.787" 3.5 times greater cutting capability Ad= .10" .079 .157 .315 .394

Excellent surface finish even under difficult cutting



CATALOG

FCR TYPES



CATALOG









Bore ø1.500 with helical milling

In 1050 carbon steel, very smooth cutting with a feed rate of 43 IPM and excellent squareness is achieved.

Fullcut Mill Model	BBT40-FCR20083-120			
Insert	BRG200808 (ACZ350S)			
Work Material	1050 Carbon Steel / Air blow			
Cutting Speed	492 SFM			
Feed Rate	43 IPM			
Axial DOC	.079 x 3 times			
Hole Dia.	ø1.500			





Honeycombed pocket with ramping

Low rigidity workpiece, .12 thickness clamped by a vise. Feed rate of 169 IPM on both sides of the workpiece is achieved.

Fullcut Mill Model	BBT40-FCR20083-85
Insert	BRG200808 (DS20)
Work Material	Aluminum / Air blow
Cutting Speed	2,461 SFM
Feed Rate	169 IPM
Axial DOC	.236 x 3 times
Radial DOC	Max .787



(800) 991-4225