

TurnLine

Member IMC Group  
**Tungaloy**  
INDUSTRY 4.0

**ISO E<sup>CO</sup>TURN**

[www.tungaloy.com/us](http://www.tungaloy.com/us)

Tungaloy Report No. 426S1-US

**AHB**  
TOOLING & MACHINERY

**COMPLETE  
METALWORKING  
SOLUTIONS**


(800) 991-4225

[www.ahbinc.com](http://www.ahbinc.com)

ISO Certified

[customerservice@ahbinc.com](mailto:customerservice@ahbinc.com)

**Newest turning toolholders** with  
easy insert clamping system



**INDUSTRY 4.0**  
*FEED the SPEED!*



# Enables easy and quick insert exchange

## New tool holders for VNMG2.33\*\*E (VNMG1204\*\*E) insert



**New**

- **Machine type**  
For Swiss machines
- **Features**
  - Lever lock clamping (to be clamped from the back)
  - Without offset
  - Square shanks in sizes: 0.500" X 0.500" (12X12) and 0.625" X 0.625" (16X16)
  - Insert: VNMG2.33\*\*E (VNMG1204\*\*E)


- **Machine type**  
For general CNC lathes
- **Features**
  - Standard lever lock clamping
  - With offset
  - Square shanks in sizes: **New** 0.625" X 0.625" (16X16), 0.750" X 0.750" (20X20), and 1.000" X 1.000" (25X25)
  - Insert: VNMG2.33\*\*E (VNMG1204\*\*E)




## Latest grades offer excellent cutting performance in a wide variety of applications

VNMG2.33**E (VNMG1204**E) line up			
Material	Grade		Chipbreaker
<b>P K</b>	<b>T9215</b>	CVD coating	TF / TSF / TM
<b>P</b>	<b>T9225</b>	CVD coating	TF / TSF
<b>P</b>	<b>AT9530 / GT9530 / NS9530</b>	Coated and uncoated cermets	TSF
<b>M</b>	<b>AH630 / AH645</b>	PVD coating	SS / SM
<b>M</b>	<b>T6120 / T6130</b>	CVD coating	SS / SM

## Cutting performance




- P** Insert : VNMG 2.331E TSF T9215
- Workpiece material : 1045
- Cutting speed :  $V_c = 492$  sfm
- Feed :  $f = 0.004$  ipr
- Depth of cut :  $a_p = 0.020$ "
- Coolant : Wet



## PVJNR/L-Eco

Lever-lock toolholder with 93° approach angle, for negative 35° rhombic inserts



Cutting edge style J

Right hand (R) shown.

	Inch	H	B	LF	LH	HF	WF	RE**	Insert	Torque
<b>New</b>	PVJNR/L102.33	0.625	0.625	4.000	1.380	0.625	0.875	0.031	VNMG2.33...	1.48
	Metric	H	B	LF	LH	HF	WF	RE**	Insert	Torque*
<b>New</b>	PVJNR/L1616H1204	16	16	100	35	16	20	0.8	VN**1204...	2
	PVJNR/L2020K1204	20	20	125	35	20	25	0.8	VN**1204...	2
	PVJNR/L2525M1204	25	25	150	35	25	32	0.8	VN**1204...	2

Torque: Recommended clamping torque: lbs-ft (\*N·m)

\*\*RE: The holder measurements are true with this insert radius


### SPARE PARTS

Designation	Shim	Clamping screw	Wrench	Spring pin	Lever
PVJNR/L102.33 PVJNR/L**1204	LSV212	LCS3V	P-2.5	LSP3	LCL3V

**New**

## JPVJ2NR/L-Eco

Back-clamp toolholder with 93° approach angle, for negative 35° rhombic inserts



Cutting edge style J

Without offset

Right hand (R) shown.

	Inch	H	B	LF	LH	HF	WF	RE**	Insert	Torque
	JPVJ2NR082.33	0.500	0.500	4.75	0.900	0.500	0	0.0078	VNMG2.33...	0.66
	JPVJ2NR102.33	0.625	0.625	4.75	0.900	0.625	0	0.0078	VNMG2.33...	0.66
	Metric	H	B	LF	LH	HF	WF	RE**	Insert	Torque*
	JPVJ2NR/L1212X1204	12	12	120	23	12	0	0.2	VN**1204...	0.9
	JPVJ2NR/L1616X1204	16	16	120	23	16	0	0.2	VN**1204...	0.9

Torque: Recommended clamping torque: lbs-ft (\*N·m)

\*\*RE: The holder measurements are true with this insert radius

### SPARE PARTS

Designation	Lever	Pin	Clamping screw	Wrench
JPVJ2NR/L***.33 JPVJ2NR/L**1204	SLLV-4	SL-PI-2	SR10400611	HW2.0/5RED

# Tungaloy America, Inc.

3726 N Ventura Drive, Arlington Heights, IL 60004, U.S.A.

## Tungaloy Canada

432 Elgin St. Unit 3, Brantford, Ontario N3S 7P7, Canada  
Phone: +1-519-758-5779 Fax: +1-519-758-5791  
www.tungaloy.com/ca

## Tungaloy de Mexico S.A.

C Los Arellano 113, Parque Industrial Siglo XXI Aguascalientes,  
AGS, Mexico 20290  
Phone:+52-449-929-5410 Fax:+52-449-929-5411  
www.tungaloy.com/mx



Scan for instant  
web access



To see Tungaloy product in action visit:



www.youtube.com/tungaloycorporation

Distributed by:




**TOOLING & MACHINERY**

**COMPLETE  
METALWORKING  
SOLUTIONS**

(800) 991-4225  
www.ahbinc.com  
ISO Certified  
customerservice@ahbinc.com

FIND US ON THE CLOUD!  
machiningcloud.com



Mar. 2021 (TJ)