

General System Details (more on last page)

Communication Options to SupplyPort:

- 1) LAN
- 2) Cable Modem or DSL
- 3) External USB Modem Requires analog phone line suitable for fax machine
- 4) Wireless Ethernet, via customer supplied wireless/wired bridge
- 5) Cellular Modem, provided by SupplyPro (only available in the Continental US) or via customer provided air card and compatible Ethernet router

UPS & Surge Protection for both devices and network connection (supplied by Client)

FOR SITES THAT EXPERIENCE POWER INSTABILITY A SURGE PROTECTOR IS RECOMMENDED - DEVICE REQUIRE 110V OF CLEAN POWER; Suggested model: APC Model BF500U (provides 80 minutes of life)

Manual Over-Ride: All devices have a manual over-ride to access product.

Standard Methods to log into machines * (it is always preferred to use the client's standard company badge where possible):

- Magnetic stripe or Barcode Reader
- Proximity Reader
- Biometric Fingerprint Reader
- Hand-Held Scanner

* Clients may elect that users manually log into system - card reader is optional, and/or client may elect to also attach an external keyboard

* The SupplyPad can only read a barcode style of badge (or manual login)

PRODUCT SPECIFIC

Topic	SupplyBay	SmartDrawer	Single Box Dispenser (SBD)	SupplyPod	Virtual Inventory Module
General Description	Helix coil, dispense only unit. Optional clear door with lights available.	Covers in various lid configurations and sizes; retrofit onto standard width and depth Vidmar, Lista & Rousseau cabinets. All SmartDrawer lids are clear and have individual locking for any combination of control level as required by the individual product.	SmartDrawer type, cassette style assembly; specific drawer depth req'd ** SBD is not field retrofitable **	SmartDrawer style in a compact footprint that can be mounted on a desk/bench/tool chest or to a wall	Virtual Inventory Module (VIM) allows SupplyLink & SupplyPad clients to track transactions for products not physically within the SupplyPro devices
Unit Weight (no product loaded)	451 lbs. (palletized: 606 lbs)	12 lbs per cover	SBD ASSEMBLY (108 cassettes): 75 lbs	81 lbs.	N/A
Dimensions (all listed in inches)	Unit Dimensions: 72" H x 41" W x 34 1/8" D Palletized Dimensions: 78" H x 45" W x 40" D	Stock Cabinet: SC900 - 28 1/4" W x 28 1/2" D x 39 3/8" H Various Sizes (lid opening dims; L x W): 2 Lid: 10.83" x 20.8" 4 Lid: 10.83" x 9.5" 8 Lid: 4.96" x 9.5" 12 Lid: 10.8" X 2.21" 16 Lid: 4.96" X 4.02" 24 Lid: 4.96" X 2.21" 48 Lid: 3.65" x 1.12" x 1.02" *Depth based on drawer depth	Per Cassette (Internal Dimensions): Type I: 5" x 2.36" x .75" Type II: 3.12" x 6.37" x .75" Type IV: 2.97" x 6.37" x 1.98"	22" H x 18.5" W x 14.35" D	N/A
Select User Transactions Supported	Take	Take; Return; Check In; Check Out (including Serialization)	Take; Return; Check In; Check Out (including Serialization)	Take; Return; Check In; Check Out (including Serialization)	Take; Return; Check In; Check Out (including Serialization)
Level of Control	Absolute Control	Variable - Absolute Control and/or Part Number Control	Absolute Control	Variable - Absolute Control and/or Part Number Control	Open Location(s) as defined by Client
Unit Configurability	Configurable trays and helices	Individual lids within the covers cannot be reconfigured however drawers are field reconfigurable at the cover level	Assembly is not reconfigurable & can only be installed in std width drawers as follows: Lista: Model 200 Stanley-Vidmar: Model 50	Available in 3 standard configurations - A96 or B80	N/A
Max. Capacity Per Device (# SKUs) <u>without Auxiliary Units attached</u>	60 SKUs Std 70 SKUs with 7th tray option	Based on individual cover size: 2, 4, 8, 12, 16, 24, 48 or SBD (108)	Per SBD Assembly: 108 Cassettes Type I: 96 Type II: 8 Type IV: 4	96 or 80	SupplyLink: up to 500 (one module per Link)* SupplyPad: up to 2,000 *up to 2,000 if no devices on Link
User Interface Options	SupplyLink or Keypad	SupplyLink	SupplyLink	SupplyPod Touchscreen Controller	SupplyLink; SupplyPad
Weight Capacity	80 lbs per tray 10 lbs max (w/o friction)	400 - 450 lbs per drawer (actual cap based on cabinet mfr)	1.1 lb per cassette (123.2 lbs per assembly)	40 lbs. per drawer	N/A
Electrical Requirements	Main draws 2 amp Aux draws 1 amp 120 Volts AC	Draws power through SupplyLink Cat5 cable	Draws power through SupplyLink Cat5 cable	100-240Vac 1.5A 50-60Hz	N/A

PRODUCT SPECIFIC CONTINUED

Topic	SupplyLocker	SupplyTower	SupplyLink	SupplyAgent II	SupplyPad
General Description	Modular locker door unit. Standard solid doors - optional clear door with lights available.	Standard configuration auxiliary unit; 12 solid doors that are tall and narrow; ideal for torque wrenches and similar products!	Touch screen controller; supports SmartDrawer*, SupplyBay, and SupplyLocker device types *required for SmartDrawer	Clear door unit with flexible shelf's and drawer options; take/return/checkin-out	Mobile Tablet device for barcode and RFID scanning of open stock management
Unit Weight (no product loaded)	200 lbs. lightest to 1200 lbs. Heaviest *based on module config	359 lbs.	13.5 lbs (6.12 kg)	650 lbs.	3.9 lbs. per SupplyPad
Dimensions (all listed in inches)	Overall Unit: 36" W x 76" H x 22" D (2x4) Palletized: 82" H x 45" W x 40"D * See table below for individual door dimension details	36" W x 76" H x 22" D Palletized: 81" H x 45" W x 40"D	12.17" x 12.49" x 9.08"	79" H x 52" W x 28" D Individual door: 22" W X 16" H X 25.5" D	7.4" H x 9.45" W x 1.85" D
Select User Transactions Supported	Take; Return; Check In; Check Out (including Serialization)	Take; Return; Check In; Check Out (including Serialization)	All	Take; Return; Check In; Check Out	Take; Return; Check In; Check Out (including Serialization)
Level of Control	Variable - Absolute Control and/or Part Number Control	Variable - Absolute Control and/or Part Number Control	N/A	Door Level	Open Shelf / Bin
Unit Configurability	5 door "module" types (not field reconfigurable)	Standard config - 12 doors per unit	N/A	Adjustable shelves and bin sizes	N/A
Max. Capacity Per Device (# SKUs) without Auxiliary Units attached	42 SKUs - 2x4 MAIN config with all 6 door modules 48 max SKUs per aux	12	Can support up to ~ 5 devices *actual depends on configuration	192 SKUs w/o options	up to 2,000 SKU's
User Interface Options	SupplyLink or Keypad *can be main or aux	Auxiliary Unit to SupplyLink or Keypad	Other Details for SupplyLink: Fanless Cooling System Display: 12.1" SVGA (800x600) Color TFT LCD Operating System: Window XP Embedded	Color touch screen	SupplyLink experience and functionality
Weight Capacity	200 lbs. per "module"	50 lbs. per door		150 lbs. per shelf	N/A
Electrical Requirements	Main draws 2 amp Aux draws 1 amp 120 Volts AC Else through SupplyLink	Aux draws 1 amp 120 Volts AC	Draws 30 Watts; Standard IEC 60320 C13 three-pin connector	Main draws 2 amp Aux draws 1 amp 120 Volts AC	Docking Station draws less than 2 amps



STOCK LISTA SMARTDRAWER CABINET OPTIONS (custom cabinets available that carry longer lead-times)

LISTA SC900 - Model L7			LISTA SC900 - Model L7SBD			LISTA SC900 - Model H8			LISTA SC900 - Model H10			LISTA SC1050 - Custom			Cover Lid Opening Dimensions:	
Drwr Model #	Drawer Depth		Drwr Model #	Drawer Depth		Drwr Model #	Drawer Depth		Drwr Model #	Drawer Depth		Model #	Drawer Depth			
Drawer 1	100	2 7/8"	Drawer 1	100	2 7/8"	Drawer 1	100	2 7/8"	Drawer 1	75	1.875"	Drawer 1			48	3.65" x .1.12" x 1.01"
Drawer 2	100	2 7/8"	Drawer 2	100	2 7/8"	Drawer 2	100	2 7/8"	Drawer 2	75	1.875"	Drawer 2			36	24: 3.65" x .1.12" x 1.01"
Drawer 3	100	2 7/8"	Drawer 3	200	6 7/8"	Drawer 3	100	2 7/8"	Drawer 3	75	1.875"	Drawer 3			12	7.48" x .1.12" x 1.01"
Drawer 4	100	2 7/8"	Drawer 4	100	2 7/8"	Drawer 4	100	2 7/8"	Drawer 4	75	1.875"	Drawer 4			24L	7.48" x .1.12" x 1.01"
Drawer 5	150	4 7/8"	Drawer 5	100	2 7/8"	Drawer 5	100	2 7/8"	Drawer 5	75	1.875"	Drawer 5			24	4.96" X 2.21"
Drawer 6	150	4 7/8"	Drawer 6	125	2 7/8"	Drawer 6	100	2 7/8"	Drawer 6	100	2 7/8"	Drawer 6			16	4.96" X 4.02"
Drawer 7	200	6 7/8"	Drawer 7	125	2 7/8"	Drawer 7	150	4 7/8"	Drawer 7	100	2 7/8"	Drawer 7			12	10.8" X 2.21"
	900		Drawer 8	150	4 7/8"	Drawer 8	150	4 7/8"	Drawer 8	100	2 7/8"	Drawer 8			8	4.96" x 9.50"
			Drawer 9			Drawer 9			Drawer 9	125	2 7/8"	Drawer 9			4	10.83" x 9.50"
						Drawer 10			Drawer 10	900	2 7/8"	Drawer 10			2	10.83" x 20.8"
												...etc.				

SUPPLYLOCKER DOOR DIMENSIONS (INTERNAL AND "SPACE THROUGH THE DOOR")

SupplyLocker Module Description					
"Module" Name	Module Descrip.	Door Opening Dims* (HxW)	Internal Dims (HxW)	# of Modules	# of Doors
SLM6	6 Door	7.01" x 3.44"	8.5" x 5.8"		0
SLM4	4 Door	7.01" x 6.42"	8.5" x 8.8"		0
SLM2H	2 Door Horizontal	7.01" x 15.48"	8.5" x 17.9"		0
SLM2V	2 Door Vertical	15.65" x 6.42"	17.2" x 8.8"		0
SLM1	1 Door	15.65" x 15.48"	17.2" x 17.9"		0
* Internal usable depth is 20.75"				0	0

SupplyTower Module Description			
Door Description	# of Doors per Unit	Door Opening Dimensions* (HxW)	Internal Dims (HxW)
Smallest Door	3	17.21" x 4.25"	19.85" x 5.92"
Medium Door	6	31.91" x 4.25"	34.5" x 5.92"
Tall Door	3	46.5" x 4.25"	49.16" x 5.92"
*Internal depth is 20.75" deep			



Additional General System Details

Temperature Thresholds:

Operating Temperature: 32 degrees F to 122 degrees F
 Storage Temperature: -4 degrees F to 158 degrees F
 Humidity: 5-95% RH, non-condensing